

## DTC

Cooling tower



1200kW module

- *Extremely quiet*
- *Highest energy efficiency*
- *Innovation boosting maintenance*

Commercial Documentation

# Cooling tower: DTC series

## Operating principle

Innovative cooling tower compliant with [latest hygiene standard](#) and [CTI thermal performance certified](#). Extremely quiet “Plug fans” centrifugal fans suck in air to cool the water optimally distributed over the exchange surface. Entirely designed to optimize its ease of maintenance thanks to its integrated technical room, the [DTC](#) is a concentrate of energy efficiency, even in case of space constraints with the possibility of installation in a corner


## Hygienic design: compliant with European hygienic standard

Optimized accessibility: the technical room integrated into the tower offers total and immediate access to all the internal parts of the tower: drip eliminators, exchange bodies, water distribution ramps, basin with its accessories, motors, and fans.

[Maintenance](#) is [simplified](#), even while [DTC](#) operating.




Casing: self-supporting panels casing have been twice or 4 times folded over the 4 sides ([JACIR](#) design) allowing additional sound attenuation casing if required. Thanks to this technology, we offer cooling towers with an extremely low sound level. Towers are assembled with waterproof stainless-steel rivets (uniform, high-capacity locking). There is no welding on assembled panels for the parts in contact with water. [DTC](#) range cooling towers are designed for an optimized transport and final assembly of its 2 modules.




Basin: the bottom of the basin is inclined for [complete draining and fully accessible](#) through the integrated technical room with dedicated access door. It includes an easily adjustable float valve, an overflow, an anti-freeze resistance as well as an anti-cavitation stainless-steel + HDPE strainer.

## Exchange surface : WAVE-PACK

Made of straight corrugated PVC channels and designed for continuous water temperatures of up to 55°C as standard. A high-temperature packing option in PP is available, allowing operation up to 75°C. When assembled, it forms channels with a cross-section of 25 mm. This technology combines an extended exchange surface with high fouling resistance and very low pressure drops, thanks to its vertical channel design.



## “Plug fans” motor fan set



- ∞ First cooling towers equipped with single sided air inlet [centrifugal jet fans](#),
- ∞ Efficiency of electronically commutated motors superior to IE5,
- ∞ Direct transmission: no mechanical maintenance,
- ∞ “[Plug and Play](#)”: integrated wiring, connection, and speed variation,
- ∞ High pressure drops available on the ai (for ducts and silencers).



Compliant with ecoconception (UE) 327/2011 concerning Directive 2009/125/CE application (ErP) for minimum efficiency thresholds after 2015.

## Water distribution

PVC water distribution pipes feed the polypropylene nozzles (easily removable stainless-steel screws) equipped with internal turbulators for an optimal water distribution.



## Ultra-silence



- ∞ 64dBA at 3m for 1,2MW
- ∞ Equivalent to a centrifugal forced draft cooling tower equipped with sound attenuations.
- ∞ Improved competitiveness and power consumption